

6.2 RS-2 One Unit (Small Lot) Residential Zone

The intent of this zone is to accommodate one unit residential *buildings* on *lots* of 362 square metres (3,896.53 square feet) or more.

6.2.1 Permitted Uses:

- 1) a *one-unit residential* use in conjunction with not more than one (1) of the following accessory uses:
 - a) an *accessory child care centre* in accordance with the provisions of Section 5.1.
 - b) an *accessory boarding use* in accordance with the provisions of Section 5.4.
 - c) an *accessory registered secondary suite* in accordance with the provisions of Section 5.5.
 - d) an *accessory bed & breakfast use* in accordance with the provisions of Section 5.7.
 - e) an *accessory vacation rental* in accordance with the provisions of Section 5.8.
- 2) an *accessory home occupation* in conjunction with a *one-unit residential use* and in accordance with the provisions of Section 5.3;
- 3) a *care facility* in accordance with the provisions of Section 5.1.
- 4) notwithstanding the above, on lots with less than the minimum required *lot area*, a one-unit residential use only is permitted.
- 5) notwithstanding 1) above, both an *accessory bed and breakfast use* and an *accessory vacation rental* may be permitted in combination and operated as a single business when limited to a maximum combination of four (4) *sleeping units* and eight (8) adult guests.

6.2.2 Lot Size:

- 1) The minimum *lot width*, *lot depth* and *lot area* in the RS-2 zone are as follows:

Lot width	10.0m (32.81ft)
Lot depth	27.4m (89.9ft)
Lot area	362.0m ² (3,896.53ft ²)

6.2.3 Lot Coverage:

- 1) The maximum *lot coverage* in the RS-2 zone is 50%.

6.2.4 Floor Area:

- 1) maximum *residential gross floor area* shall not exceed 0.6 times the *lot area*.

6.2.5 Building Heights:

- 1) *principal buildings* shall not exceed a *height* of 7.7m (25.26ft), and the height of the southerly elevation of the building shall be determined by an angle of containment of 45 degrees to the vertical commencing 6.0 metres (19.69 feet) above the natural grade at the base of the south wall as illustrated in sub-section 4.9.
- 2) *ancillary buildings* and structures shall not exceed a *height* of 4.0m (13.12ft).

6.2.6 Minimum Setback Requirements:

- 1) *principal buildings* and *ancillary buildings and structures* in the RS-2 zone shall be sited in accordance with the following minimum *setback* requirements:

Setback	Principal Building	Ancillary Buildings and Structures
Front lot line i.e. see 2) below	3.0m (9.84ft)	Not permitted
Rear lot line i.e. see 2) below	3.0m (9.84ft)	1.5m (4.92ft)
Interior side lot line	1.2m (3.94ft)	1.2m (3.94ft)
Interior side lot line (abutting a lane)	2.4m (7.87ft)	2.4m (12.47ft)
Exterior side lot line (rear lot line abutting a lane or rear lot line of adjacent lot) i.e. for a distance of 7.5m as per 3) below	3.0m (9.84ft) & 1.5m (4.92ft)	3.0m (9.84ft) & 1.5m (4.92ft)

- 2) Notwithstanding the above, the *front and rear yard setbacks* shall in combination be not less than 12.0m (39.37ft).
- 3) Notwithstanding the above, the *exterior side yard setback* requirement for *principal buildings* and for *ancillary buildings and structures* shall be 3.0m (9.84ft) for a distance of 7.5m (24.61ft) from the *front lot line* and 1.5m (4.93ft) from that point to the *rear lot line* of the *lot*.

6.2.7 Ancillary Buildings and Structures:

Except as otherwise provided in Section 4.14 and in addition to the provisions of subsections 6.2.5 and 6.2.6 above, the following also applies:

- 1) there shall be not more than one *ancillary building per lot*.
- 2) *ancillary buildings* shall not exceed a gross floor area of 11.15m² (120.0ft²).
- 3) *ancillary buildings and structures* shall not be located in any required *front yard* or *exterior side yard* area.

6.2.8 Accessory off-street parking shall be provided in accordance with the provisions of Section 4.15.